







KERA RANGE KE60UT

TYPE	Undercounter dishwasher
LINE	KERA RANGE
BASKET	500x600
SIZE	585x715x865

The warewashers of the Kera range combine **technology**, **design** and **excellent performance** with a strong focus on **sustainability**. Equipped with the latest technology as standard, they guarantee perfect washing and impeccable hygiene in every cycle. Thanks to **Integrated Bluetooth and Wi-Fi connectivity**, each model can be fully managed remotely via the **Krupps Remote Control** app and **iKloud** digital platform.

The Kera range is designed to offer you maximum cleanliness with a savings of over 30% on daily energy consumption.

The multifunctional dishwasher full optional KE60UT is the ideal resource for professionals who need to handle a large number of dishes in limited space.

The **KE60UT** model stands out for its **sophisticated design**, its **excellent performance** and its **versatility**; thanks to its **working height of 405mm** it allows the washing of GN1/1 trays up to 650mm high, 600x400mm cassettes and pastry trays, while maintaining the dimensions of a practical undercounter.

The **innovative 5? TFT touchscreen display** allows total control over every step and maximum customisation of washing cycles. The **Acquatech System technology** ensures constant temperature, pressure and consumption, while the "**Level Control**" **self-regulating system** keeps the water level in the tank uniform, guaranteeing impeccable cleaning.

[A[C€ ⊕

WRAS APPROVED PRODUCT










DISHWASHERS FEATURES	KERA RANGE KE60UT
Dimensions - (mm) L - P - H	585x715x865
n° baskets/hour - (+55°C)	Max 40
Height glass max	360mm
Ø height plate max	385mm
Height pot max	360mm
Trays	GN1/1 - 60x40
Tank heating element - Tank capacity	2,6kW - 30lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,9kW / 1,2Hp
Total power input / Current	6,52kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
ACCESSORI	
Cutlery insert	2
Basket for trays 10/12 compartments 500x600x100mm	1
Basket for glasses dim.500x600x100mm	1
Basket for 22 dishes dim.500x600x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	
Reverse osmosis system	•
Inclined basket for wine glasses dim.500x500x170mm	•
Kit 4 Stainless steel feet 50-70mm	•
"SOFT Door" Opening/Closing System	-
Start Cycle "SOFT Start"	

KE60UT



WRAS APPROVED PRODUCT

